SHAFT PERFORMANCE MATRIX **ZXiIRONS**

Use the chart on the right to select an available Iron shaft that provides just the right launch and spin characteristics for any player. And, while this chart reveals the relative performance of many shafts in our Custom Catalog, remember that every player loads and releases shafts uniquely.

				WEIGH	WEIGHT CLASS				
			ULTRA-LIGHTWEIGHT	LIGHTWEIGHT	MIDWEIGHT				
		HIGH	KBS MAX 45* KBS MAX 50* KBS MAX 55* Helium Nanocore 50* Helium Nanocore 60*	KBS MAX 85 KBS MAX 65* KBS MAX 80 HL N.S. Pro 750GH Neo	KBS Tour Lite				
		MID-HIGH	KBS TGI 60*	KBS 560 (Jr Shafts) KBS 580 (Jr Shafts) SteelFiber i70cw*	KBS C-Taper Lite				
	LAUNCH/SPIN	MID	KBS TGI 60*	KBS TGI 80* KBS TGI 90* KBS TGI 95* MMT 65* MMT 85* Recoil Dart 65* Recoil Dart 75* SteelFiber fc90cw* SteelFiber i80cw*	KBS TGI 100* KBS Tour-V Dynamic Gold 105 Dynamic Gold Mid 100 Dynamic Gold Mid 115 N.S. Pro Modus3 Tour 105				
		LOW-MID		SteelFiber i95cw*	AXIOM 105* MMT 105* SteelFiber i110cw*				
fts e) ey er.		MOJ							

Srixon Stock Shafts Custom Shafts Graphite Shafts*

Notes: Because every player loads and releases shaf differently, the chart on the right is a relative (not absolute measure of how each shaft performs, and how the perform relative to each othe

IRONS - CUSTOM SPECIFICATIONS

MODELS	LENGTH ADJUSTMENT*	LIE ADJUSTMENTS	LOFT ADJUS	TMENTS	SHAFT STEPPING		GRIP AND WRAPS							
ZXi7 ZXi5 ZXi4	-2" to +2"	-3° to +3° (LH -2° to +2° only)	-2° to +	-2° to +2°		Hard Step Soft Step		 1 to 3 Extra Wraps 1 to 3 Extra Lower Wraps Grip Logo Down Grip Logo Down +1 to 3 Extra Wraps 						
ZXi Utility	-1" to +1"	-2° to +2°					Grip Logo Down +1 to 3 Extra Lower Wraps Uninstalled/In Box							
RIXON STANDARD BUILD LENGTHS (INCHES)														
	2i		4i 5i	6i	7i	8i	9i	PW	AW					
All Srixon Irons		3i		<mark>6</mark> i 37.75"	<mark>7</mark> i 37.25"	<mark>8</mark> i 36.75"	<mark>9i</mark> 36.25"	PW 35.75"	AW 35.75					

This shaft configuration is designed to maximize performance for the Srixon and Cleveland Iron Sets. Strong-stepped custom onfigurations are also available for most shafts. For all custom ron shafts, traditional soft-stepping and strong-stepping custom configurations are available. Please contact Srixon/Cleveland Golf ustomer Experience at (800) 999-6263 if you have any questions.



Srixon Utilities and Irons accept .355 taper tip shafts.

*Any custom RH order 1/2" overlength or longer on ZXi7, and ZXi5 rons will be built with a lighter designed head. Lighter heads range from 2-4g lighter than standard heads.